

Jar Tester



SF-06



SF-04

1 Features

- The use of a timing belt synchronizes the revolutions of the size paddles so that relative errors are eliminated
- Digital display of the rpm, and forward, reverse & automatic control
- Low noise at the high speed of brushless DC motor

2 Specifications

Model	SF-04	SF-06
Paddle	Dia.40mm x 4	Dia.40mm x 6
Blade	1" x 3", stainless steel	
RPM	20 to 300	
Drive	Brushless DC motor 60W	
Timer	Digital / 99hr,59min,59sec	
Illumination	FL 20W x 2	
Control & display	Microprocessor & digital LED display	
Power source	220VAC, 50/60Hz	
Overall (WxDxH)	320x320x390mm	900x250x450mm
Weight (Kg)	10	22

Melting Point Apparatus



MPA-30

1 Features

- This unit features SSR control of oven temp. and readout digitally
- Built-in holding function of melting point temperature
- Simply press a key to display temperature into temporary memory.
- Magnifying lens and illuminator permit clear viewing

2 Specifications

Model	MPA-30
Top plate	Dia. 30 mm
Temp. range	Up to 350°C
Temp. control	SSR control with 100W heater
Display	Analog controller & digital display
Power source	220VAC, 50/60Hz
Overall (WxDxH)	200x195x230mm
Weight (Kg)	8

Electro Analyzer



EA-300

1 Features

- Metal ion such as Ni, Cu, Pb, Sb & Zn can be detected and analyzed
- Built-in heater and stirrer speed can be regulated by automatically
- Voltage and current can be smoothly varied.

2 Specifications

Model	EA300
Heater	300 Watt
Speed	0 - 60 rpm / 6 W motor
Voltage range	DC 0 - 10V
Ampere range	DC 0 -1A / 1 - 10A
Function	Ampere, Speed & Temp. controller
Control	Analog / Dial knob
Material	Powder coated steel case & SUS work table
Power source	220VAC, 50/60Hz, single phase, 1.4A
Overall (WxDxH)	355x375x615mm
Weight (Kg)	23.5