

## Jar Tester

SF04 / 06



SF-06



SF-04

### 1 Features

- The use of a timing belt synchronizes the revolutions of the size paddles so that relative errors are eliminated
- Digital display of the rpm, and forward, reverse & automatic control
- Low noise at the high speed of brushless DC motor

### 2 Specifications

Model	SF-04	SF-06
Paddle	Dia.40mm x 4	Dia.40mm x 6
Blade	1" x 3", stainless steel	
RPM	20 to 300	
Drive	Brushless DC motor 60W	
Timer	Digital / 99hr,59min,59sec	
Illumination	FL 20W x 2	
Control & display	Microprocessor & digital LED display	
Electric power	220VAC, 50/60Hz	
Overall (WxDxH)	320x320x390mm	900x250x450mm
Weight (Kg)	10	22

## Melting Point Apparatus

MPA-30



### 1 Features

- This unit features SSR control of oven temp. and readout digitally
- Built-in holding function of melting point temperature
- Simply press a key to display temperature into temporary memory.
- Magnifying lens and illuminator permit clear viewing

### 2 Specifications

Model	MPA-30
Top plate	Dia. 30 mm
Temp. range	Up to 350 °C
Temp. control	SSR control with 100W heater
Display	Analog controller & digital display
Electric power	220VAC, 50/60Hz
Overall (WxDxH)	200x195x230mm
Weight	8 Kg

## Freezing Point Tester

HB series



### 1 Features

- This unit use for testing the freezing point of liquid materials.
- The sample holder and clamp help to settle the sample easy.
- Viewing door is convenience to find the freezing point

### 2 Specifications

Model	HB-807F
Chamber (WxDxH)	350x350x350(mm)
Temp.range	0 to - 60°C +/-1 at 50 °C
Speed range	0 - 400 rpm
Refrigerator	2 stage of 1/3Hp & Non-CFC refrigerant
Sample hole	Dia. 40 mm x 5 ea
Material	Stainless steel interior & steel plate exterior
Safety device	Over load limiter, over current breaker
Control & display	Microprocessor PID control & digital LED display
Electric power	220VSC, 50/60Hz, 800W
Overall (WxDxH)	650x650x700H(mm)
Weight	30 Kg